

JB/BT 020-2004 附表1-1

JB/BT 021-2004-A附表: 10mm片宽散热器技术参数 (涂漆产品)

散热片数	12				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m ²	m ²	m ²	kg	kg
1000	6.4	7.5	11.6	113.2	35.6
1200	7.7	8.9	13.9	131.3	41.1
1250	8.0	9.3	14.5	136.0	42.5
1400	8.9	10.4	16.3	149.6	46.7
1500	9.6	11.1	17.5	158.7	49.5
1600	10.2	11.8	18.7	167.8	52.3
1750	11.1	12.9	20.4	181.4	56.5
1800	11.4	13.3	21.0	185.9	57.8
2000	12.7	14.7	23.4	204.2	63.4
2200	13.9	16.2	25.8	222.5	69.0
2250	14.2	16.6	26.3	227.0	70.4
2400	15.2	17.7	28.1	240.6	74.5
2500	15.8	18.4	29.3	249.8	77.3
2600	16.4	19.1	30.5	258.9	80.1
2750	17.4	20.2	32.3	272.5	84.3
2800	17.7	20.6	32.9	277.1	85.7
3000	18.9	22.0	35.2	295.2	91.2
3200	20.2	23.5	37.6	313.5	96.8
3250	20.5	23.9	38.2	318.0	98.2
3400	21.4	24.9	39.9	331.7	102.4
3500	22.0	25.7	41.1	340.8	105.2
3600	22.6	26.4	42.3	349.8	107.9
3750	23.6	27.5	44.1	363.6	112.1
3800	23.9	27.9	44.7	368.1	113.5
4000	25.1	29.3	47.0	386.3	119.1
4200	26.4	30.8	49.4	404.5	124.6
4250	26.7	31.1	50.0	409.2	126.0
4400	27.6	32.2	51.8	422.8	130.2
4500	28.3	33.0	53.0	431.9	133.0
4600	28.9	33.7	54.1	441.0	135.8
4750	29.8	34.8	55.9	451.6	139.9

散热片数	14				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	7.4	8.6	13.5	129.6	40.9
1200	8.8	10.3	16.2	150.8	47.4
1250	9.2	10.7	16.9	156.2	49.0
1400	10.3	11.9	19.0	172.0	53.9
1500	11.0	12.8	20.4	182.7	57.1
1600	11.7	13.6	21.8	193.3	60.4
1750	12.8	14.9	23.8	209.2	65.2
1800	13.1	15.3	24.5	214.5	66.9
2000	14.6	17.0	27.3	235.7	73.4
2200	16.0	18.7	30.0	257.2	79.9
2250	16.4	19.1	30.7	262.4	81.5
2400	17.4	20.3	32.8	278.3	86.4
2500	18.2	21.2	34.2	288.9	89.6
2600	18.9	22.0	35.6	299.6	92.8
2750	20.0	23.3	37.6	315.4	97.7
2800	20.3	23.7	38.3	320.8	99.3
3000	21.7	25.4	41.1	342.0	105.8
3200	23.2	27.0	43.8	363.3	112.3
3250	23.5	27.5	44.5	368.5	113.9
3400	24.6	28.7	46.6	384.5	118.8
3500	25.3	29.6	48.0	395.2	122.1
3600	26.0	30.4	49.4	405.7	125.3
3750	27.1	31.7	51.4	421.7	130.2
3800	27.5	32.1	52.1	426.9	131.8
4000	28.9	33.8	54.9	448.2	138.3
4200	30.3	35.4	57.6	469.5	144.8
4250	30.7	35.9	58.3	474.9	146.4
4400	31.8	37.1	60.4	490.8	151.3
4500	32.5	38.0	61.8	501.4	154.5
4600	33.2	38.8	63.2	512.0	157.8
4750	34.3	40.1	65.2	524.9	162.7

散热片数	16				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	8.4	9.7	15.4	146.0	46.2
1200	10.0	11.6	18.6	170.2	53.6
1250	10.4	12.1	19.3	176.4	55.5
1400	11.6	13.5	21.7	194.5	61.1
1500	12.5	14.5	23.3	206.7	64.8
1600	13.3	15.4	24.9	218.8	68.5
1750	14.5	16.9	27.2	237.0	74.0
1800	14.9	17.4	28.0	243.0	75.9
2000	16.5	19.3	31.2	267.3	83.3
2200	18.1	21.2	34.3	291.8	90.7
2250	18.5	21.6	35.1	297.8	92.6
2400	19.8	23.1	37.5	315.9	98.2
2500	20.6	24.0	39.1	328.1	101.9
2600	21.4	25.0	40.6	340.2	105.6
2750	22.6	26.4	43.0	358.4	111.1
2800	23.0	26.9	43.8	364.6	113.0
3000	24.6	28.8	46.9	388.7	120.4
3200	26.3	30.7	50.1	413.0	127.8
3250	26.7	31.2	50.9	419.0	129.7
3400	27.9	32.6	53.2	437.3	135.3
3500	28.7	33.5	54.8	449.5	139.0
3600	29.5	34.5	56.4	461.5	142.7
3750	30.7	35.9	58.8	479.8	148.3
3800	31.1	36.4	59.6	485.8	150.1
4000	32.8	38.3	62.7	510.1	157.5
4200	34.4	40.2	65.9	534.4	165.0
4250	34.8	40.7	66.7	540.6	166.8
4400	36.0	42.1	69.0	558.8	172.4
4500	36.8	43.1	70.6	570.9	176.1
4600	37.6	44.0	72.2	583.1	179.8
4750	38.9	45.4	74.5	598.2	185.4

散热片数	18				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	9.4	10.9	17.3	162.4	51.5
1200	11.2	13.0	20.9	189.6	59.9
1250	11.6	13.5	21.8	196.5	62.0
1400	13.0	15.1	24.4	217.0	68.2
1500	13.9	16.2	26.2	230.6	72.4
1600	14.8	17.3	28.0	244.3	76.6
1750	16.2	18.9	30.6	264.7	82.8
1800	16.6	19.4	31.5	271.5	84.9
2000	18.4	21.5	35.1	298.9	93.3
2200	20.3	23.6	38.6	326.4	101.6
2250	20.7	24.2	39.5	333.1	103.7
2400	22.1	25.8	42.2	353.6	110.0
2500	23.0	26.8	43.9	367.2	114.1
2600	23.9	27.9	45.7	380.9	118.3
2750	25.2	29.5	48.4	401.3	124.6
2800	25.7	30.0	49.3	408.3	126.7
3000	27.5	32.2	52.8	435.4	135.0
3200	29.3	34.3	56.3	462.8	143.4
3250	29.8	34.8	57.2	469.5	145.5
3400	31.1	36.4	59.9	490.2	151.7
3500	32.0	37.5	61.7	503.8	155.9
3600	33.0	38.5	63.4	517.3	160.1
3750	34.3	40.1	66.1	537.9	166.3
3800	34.8	40.7	67.0	544.7	168.4
4000	36.6	42.8	70.5	572.0	176.8
4200	38.4	44.9	74.1	599.4	185.1
4250	38.8	45.5	75.0	606.3	187.2
4400	40.2	47.1	77.6	626.8	193.5
4500	41.1	48.1	79.4	640.4	197.6
4600	42.0	49.2	81.2	654.1	201.8
4750	43.4	50.8	83.8	671.5	208.1

散热片数	20				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	10.3	11.9	19.2	178.8	56.8
1200	12.3	14.3	23.2	209.0	66.1
1250	12.8	14.9	24.2	216.7	68.4
1400	14.3	16.6	27.1	239.4	75.4
1500	15.3	17.8	29.1	254.6	80.0
1600	16.3	19.0	31.1	269.8	84.7
1750	17.8	20.7	34.0	292.5	91.6
1800	18.2	21.3	35.0	300.0	94.0
2000	20.2	23.6	38.9	330.4	103.2
2200	22.2	26.0	42.9	361.0	112.5
2250	22.7	26.6	43.9	368.5	114.8
2400	24.2	28.3	46.8	391.2	121.8
2500	25.2	29.5	48.8	406.4	126.4
2600	26.2	30.6	50.8	421.6	131.1
2750	27.7	32.4	53.7	444.3	138.0
2800	28.2	33.0	54.7	452.0	140.3
3000	30.2	35.3	58.7	482.2	149.6
3200	32.2	37.7	62.6	512.6	158.9
3250	32.7	38.2	63.6	520.1	161.2
3400	34.2	40.0	66.5	543.0	168.2
3500	35.2	41.2	68.5	558.2	172.8
3600	36.2	42.3	70.5	573.2	177.4
3750	37.7	44.1	73.4	596.1	184.4
3800	38.2	44.7	74.4	603.6	186.7
4000	40.1	47.0	78.4	634.0	196.0
4200	42.1	49.3	82.3	664.3	205.3
4250	42.6	49.9	83.3	672.0	207.6
4400	44.1	51.7	86.3	694.7	214.5
4500	45.1	52.8	88.2	709.9	219.2
4600	46.1	54.0	90.2	725.1	223.8
4750	47.6	55.8	93.2	744.8	230.8

散热片数	22				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	11.2	13.0	21.2	195.2	62.2
1200	13.3	15.5	25.5	228.5	72.4
1250	13.9	16.2	26.6	236.9	74.9
1400	15.5	18.1	29.8	261.9	82.6
1500	16.6	19.3	32.0	278.6	87.7
1600	17.7	20.6	34.2	295.3	92.8
1750	19.3	22.5	37.4	320.3	100.4
1800	19.8	23.2	38.5	328.5	103.0
2000	22.0	25.7	42.8	362.0	113.2
2200	24.2	28.2	47.2	395.6	123.4
2250	24.7	28.9	48.3	403.9	125.9
2400	26.3	30.8	51.5	428.8	133.6
2500	27.4	32.0	53.7	445.6	138.7
2600	28.5	33.3	55.8	462.3	143.8
2750	30.1	35.2	59.1	487.2	151.4
2800	30.6	35.9	60.2	495.7	154.0
3000	32.8	38.4	64.5	528.9	164.2
3200	35.0	40.9	68.9	562.4	174.4
3250	35.5	41.6	69.9	570.6	177.0
3400	37.1	43.5	73.2	595.8	184.6
3500	38.2	44.8	75.4	612.5	189.7
3600	39.3	46.0	77.5	629.0	194.8
3750	40.9	47.9	80.8	654.2	202.5
3800	41.5	48.6	81.9	662.4	205.0
4000	43.6	51.1	86.2	695.9	215.2
4200	45.8	53.6	90.5	729.3	225.4
4250	46.3	54.3	91.6	737.8	228.0
4400	48.0	56.2	94.9	762.7	235.6
4500	49.0	57.5	97.0	779.5	240.7
4600	50.1	58.7	99.2	796.2	245.8
4750	51.7	60.6	102.5	818.1	253.5

散热片数	24				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	12.1	14.0	23.1	211.6	67.5
1200	14.4	16.8	27.8	247.9	78.6
1250	15.0	17.4	29.0	257.1	81.4
1400	16.7	19.5	32.5	284.4	89.7
1500	17.9	20.9	34.9	302.6	95.3
1600	19.0	22.2	37.3	320.8	100.9
1750	20.8	24.3	40.8	348.1	109.2
1800	21.4	25.0	42.0	357.1	112.0
2000	23.7	27.7	46.7	393.5	123.1
2200	26.0	30.5	51.5	430.2	134.3
2250	26.6	31.1	52.6	439.2	137.1
2400	28.4	33.2	56.2	466.5	145.4
2500	29.5	34.6	58.6	484.7	151.0
2600	30.7	35.9	60.9	502.9	156.5
2750	32.5	38.0	64.5	530.2	164.9
2800	33.0	38.7	65.6	539.4	167.7
3000	35.4	41.4	70.4	575.7	178.8
3200	37.7	44.2	75.1	612.1	189.9
3250	38.3	44.8	76.3	621.1	192.7
3400	40.0	46.9	79.8	648.6	201.1
3500	41.2	48.3	82.2	666.8	206.6
3600	42.4	49.6	84.6	684.8	212.2
3750	44.1	51.7	88.1	712.3	220.5
3800	44.7	52.4	89.3	721.3	223.3
4000	47.0	55.1	94.0	757.8	234.5
4200	49.4	57.9	98.8	794.3	245.6
4250	49.9	58.5	99.9	803.5	248.4
4400	51.7	60.6	103.5	830.7	256.7
4500	52.9	62.0	105.9	849.0	262.3
4600	54.0	63.3	108.2	867.2	267.8
4750	55.8	65.4	111.8	891.4	276.2

JB/BT 020-2004 附表1-2

散热片数	散热片数	26				
中心距L	中心距	有效面积		实际面积	重量	油重
		S自	S风			
mm	mm	m2	m2	m2	kg	kg
1000	1000.0	12.9	15.0	25.0	228.0	72.8
1200	1200.0	15.4	17.9	30.1	267.3	84.9
1250	1250.0	16.0	18.7	31.4	277.3	87.9
1400	1400.0	17.9	20.9	35.2	306.8	96.9
1500	1500.0	19.1	22.3	37.8	326.6	102.9
1600	1600.0	20.4	23.8	40.4	346.3	109.0
1750	1750.0	22.3	26.0	44.2	375.8	118.0
1800	1800.0	22.9	26.7	45.5	385.6	121.0
2000	2000.0	25.4	29.7	50.6	425.1	133.1
2200	2200.0	27.9	32.6	55.7	464.9	145.2
2250	2250.0	28.5	33.4	57.0	474.6	148.2
2400	2400.0	30.4	35.6	60.9	504.1	157.2
2500	2500.0	31.6	37.0	63.4	523.9	163.2
2600	2600.0	32.9	38.5	66.0	543.6	169.3
2750	2750.0	34.7	40.7	69.8	573.1	178.3
2800	2800.0	35.4	41.4	71.1	583.1	181.3
3000	3000.0	37.9	44.4	76.2	622.4	193.4
3200	3200.0	40.4	47.3	81.4	661.9	205.4
3250	3250.0	41.0	48.0	82.6	671.6	208.5
3400	3400.0	42.9	50.2	86.5	701.4	217.5
3500	3500.0	44.1	51.7	89.1	721.2	223.5
3600	3600.0	45.4	53.2	91.6	740.7	229.6
3750	3750.0	47.2	55.4	95.5	770.4	238.6
3800	3800.0	47.8	56.1	96.7	780.2	241.6
4000	4000.0	50.3	59.0	101.9	819.7	253.7
4200	4200.0	52.8	62.0	107.0	859.2	265.7
4250	4250.0	53.5	62.7	108.3	869.2	268.8
4400	4400.0	55.3	64.9	112.1	898.7	277.8
4500	4500.0	56.6	66.4	114.7	918.5	283.8
4600	4600.0	57.8	67.8	117.2	938.2	289.9
4750	4750.0	59.7	70.0	121.1	964.7	298.9

散热片数	28				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	13.7	16.0	26.9	244.5	78.1
1200	16.4	19.1	32.4	286.7	91.1
1250	17.1	19.9	33.8	297.5	94.3
1400	19.0	22.2	37.9	329.3	104.1
1500	20.4	23.8	40.7	350.5	110.6
1600	21.7	25.4	43.5	371.8	117.1
1750	23.7	27.7	47.6	403.6	126.8
1800	24.4	28.5	49.0	414.1	130.1
2000	27.0	31.6	54.5	456.6	143.0
2200	29.7	34.7	60.0	499.5	156.0
2250	30.3	35.5	61.4	510.0	159.3
2400	32.3	37.9	65.5	541.8	169.0
2500	33.7	39.4	68.3	563.0	175.5
2600	35.0	41.0	71.1	584.3	182.0
2750	37.0	43.3	75.2	616.1	191.7
2800	37.6	44.1	76.6	626.9	195.0
3000	40.3	47.2	82.1	669.1	208.0
3200	43.0	50.4	87.6	711.7	221.0
3250	43.6	51.1	89.0	722.2	224.2
3400	45.6	53.5	93.1	754.2	234.0
3500	46.9	55.0	95.9	775.5	240.4
3600	48.3	56.6	98.7	796.5	246.9
3750	50.3	58.9	102.8	828.6	256.7
3800	50.9	59.7	104.2	839.1	259.9
4000	53.6	62.9	109.7	881.6	272.9
4200	56.2	66.0	115.2	924.2	285.9
4250	56.9	66.8	116.6	934.9	289.2
4400	58.9	69.1	120.7	966.7	298.9
4500	60.2	70.7	123.5	988.0	305.4
4600	61.6	72.2	126.3	1009.3	311.9
4750	63.5	74.6	130.4	1038.0	321.6

散热片数	30				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	14.5	16.9	28.8	260.9	83.4
1200	17.4	20.2	34.7	306.1	97.3
1250	18.1	21.1	36.2	317.7	100.8
1400	20.2	23.5	40.7	351.7	111.3
1500	21.6	25.2	43.6	374.5	118.2
1600	23.0	26.9	46.6	397.3	125.2
1750	25.1	29.3	51.0	431.4	135.6
1800	25.8	30.2	52.5	442.6	139.1
2000	28.6	33.5	58.4	488.2	153.0
2200	31.4	36.8	64.3	534.1	166.9
2250	32.1	37.6	65.8	545.3	170.4
2400	34.2	40.1	70.2	579.4	180.8
2500	35.6	41.7	73.2	602.2	187.8
2600	37.0	43.4	76.1	625.0	194.7
2750	39.2	45.9	80.6	659.0	205.2
2800	39.9	46.7	82.0	670.6	208.7
3000	42.7	50.0	88.0	715.9	222.6
3200	45.5	53.3	93.9	761.5	236.5
3250	46.2	54.2	95.4	772.7	240.0
3400	48.3	56.6	99.8	807.0	250.4
3500	49.7	58.3	102.7	829.8	257.4
3600	51.1	60.0	105.7	852.3	264.3
3750	53.2	62.4	110.1	886.7	274.8
3800	53.9	63.3	111.6	897.9	278.2
4000	56.7	66.6	117.5	943.5	292.1
4200	59.6	69.9	123.4	989.1	306.1
4250	60.3	70.7	124.9	1000.7	309.5
4400	62.4	73.2	129.4	1034.7	320.0
4500	63.8	74.8	132.3	1057.5	326.9
4600	65.2	76.5	135.3	1080.3	333.9
4750	67.3	79.0	139.7	1111.3	344.3

散热片数	32				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	15.3	17.8	30.7	277.3	88.7
1200	18.3	21.3	37.1	325.6	103.6
1250	19.0	22.2	38.6	337.9	107.3
1400	21.3	24.8	43.4	374.2	118.4
1500	22.7	26.6	46.5	398.5	125.8
1600	24.2	28.3	49.7	422.8	133.3
1750	26.5	30.9	54.4	459.1	144.4
1800	27.2	31.8	56.0	471.1	148.1
2000	30.2	35.3	62.3	519.8	163.0
2200	33.1	38.8	68.6	568.7	177.8
2250	33.9	39.7	70.2	580.7	181.5
2400	36.1	42.3	74.9	617.0	192.6
2500	37.6	44.0	78.1	641.3	200.1
2600	39.1	45.8	81.2	665.7	207.5
2750	41.3	48.4	85.9	702.0	218.6
2800	42.0	49.3	87.5	714.3	222.3
3000	45.0	52.7	93.8	762.6	237.2
3200	48.0	56.2	100.1	811.2	252.0
3250	48.7	57.1	101.7	823.2	255.7
3400	50.9	59.7	106.4	859.9	266.9
3500	52.4	61.5	109.6	884.2	274.3
3600	53.9	63.2	112.7	908.2	281.7
3750	56.1	65.8	117.5	944.8	292.8
3800	56.8	66.7	119.1	956.8	296.5
4000	59.8	70.2	125.4	1005.4	311.4
4200	62.8	73.7	131.7	1054.1	326.2
4250	63.5	74.6	133.2	1066.4	329.9
4400	65.7	77.2	138.0	1102.7	341.1
4500	67.2	78.9	141.1	1127.0	348.5
4600	68.7	80.7	144.3	1151.3	355.9
4750	70.9	83.3	149.0	1184.6	367.0

散热片数	34				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	16.1	18.7	32.7	293.7	94.1
1200	19.2	22.4	39.4	345.0	109.8
1250	20.0	23.3	41.0	358.1	113.8
1400	22.3	26.1	46.1	396.7	125.6
1500	23.9	27.9	49.4	422.5	133.5
1600	25.4	29.7	52.8	448.3	141.4
1750	27.8	32.5	57.8	486.9	153.2
1800	28.6	33.4	59.5	499.6	157.1
2000	31.7	37.1	66.2	551.3	172.9
2200	34.8	40.7	72.9	603.3	188.7
2250	35.6	41.7	74.6	616.1	192.6
2400	37.9	44.4	79.6	654.7	204.4
2500	39.5	46.2	82.9	680.5	212.3
2600	41.0	48.1	86.3	706.3	220.2
2750	43.3	50.8	91.3	744.9	232.0
2800	44.1	51.7	93.0	758.0	236.0
3000	47.2	55.4	99.7	809.3	251.8
3200	50.4	59.1	106.4	861.0	267.5
3250	51.1	60.0	108.1	873.7	271.5
3400	53.5	62.7	113.1	912.7	283.3
3500	55.0	64.6	116.4	938.5	291.2
3600	56.6	66.4	119.8	964.0	299.1
3750	58.9	69.1	124.8	1002.9	310.9
3800	59.7	70.1	126.5	1015.7	314.8
4000	62.8	73.7	133.2	1067.3	330.6
4200	65.9	77.4	139.9	1119.0	346.4
4250	66.7	78.3	141.6	1132.1	350.3
4400	69.0	81.1	146.6	1170.7	362.1
4500	70.6	82.9	150.0	1196.5	370.0
4600	72.1	84.7	153.3	1222.4	377.9
4750	74.5	87.5	158.3	1257.9	389.7

散热片数	35				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	16.5	19.2	33.6	301.9	96.7
1200	19.7	22.9	40.5	354.7	113.0
1250	20.5	23.9	42.2	368.2	117.0
1400	22.8	26.7	47.4	407.9	129.2
1500	24.4	28.6	50.9	434.5	137.3
1600	26.0	30.4	54.3	461.1	145.4
1750	28.4	33.3	59.5	500.8	157.6
1800	29.2	34.2	61.2	513.9	161.7
2000	32.4	37.9	68.1	567.1	177.9
2200	35.6	41.7	75.0	620.6	194.1
2250	36.4	42.6	76.7	633.8	198.2
2400	38.8	45.4	81.9	673.5	210.4
2500	40.4	47.3	85.4	700.1	218.5
2600	42.0	49.2	88.8	726.7	226.6
2750	44.4	52.0	94.0	766.4	238.8
2800	45.2	52.9	95.7	779.9	242.8
3000	48.3	56.7	102.6	832.7	259.1
3200	51.5	60.5	109.5	885.9	275.3
3250	52.3	61.4	111.2	899.0	279.3
3400	54.7	64.2	116.4	939.1	291.5
3500	56.3	66.1	119.9	965.7	299.6
3600	57.9	68.0	123.3	991.9	307.8
3750	60.3	70.8	128.5	1032.0	319.9
3800	61.1	71.7	130.2	1045.1	324.0
4000	64.3	75.5	137.1	1098.3	340.2
4200	67.5	79.2	144.0	1151.5	356.5
4250	68.3	80.1	145.7	1165.0	360.5
4400	70.6	83.0	150.9	1204.7	372.7
4500	72.2	84.8	154.4	1231.3	380.8
4600	73.8	86.7	157.8	1257.9	388.9
4750	76.2	89.5	163.0	1294.5	401.1

散热片数	36				
中心距L	有效面积		实际面积	重量	油重
	S自	S风			
mm	m2	m2	m2	kg	kg
1000	16.8	19.6	34.6	310.1	99.4
1200	20.1	23.5	41.7	364.4	116.1
1250	20.9	24.4	43.5	378.3	120.2
1400	23.4	27.3	48.8	419.1	132.8
1500	25.0	29.2	52.3	446.5	141.1
1600	26.6	31.1	55.9	473.8	149.5
1750	29.1	34.0	61.2	514.7	162.0
1800	29.9	35.0	63.0	528.2	166.2
2000	33.1	38.8	70.1	582.9	182.9
2200	36.4	42.6	77.2	638.0	199.6
2250	37.2	43.6	78.9	651.5	203.7
2400	39.7	46.5	84.3	692.3	216.3
2500	41.3	48.4	87.8	719.7	224.6
2600	42.9	50.3	91.4	747.0	233.0
2750	45.4	53.2	96.7	787.9	245.5
2800	46.2	54.1	98.4	801.7	249.7
3000	49.4	58.0	105.5	856.1	266.4
3200	52.7	61.8	112.6	910.8	283.0
3250	53.5	62.8	114.4	924.3	287.2
3400	55.9	65.7	119.7	965.5	299.7
3500	57.6	67.6	123.3	992.8	308.1
3600	59.2	69.5	126.8	1019.8	316.4
3750	61.6	72.4	132.2	1061.1	329.0
3800	62.5	73.3	133.9	1074.5	333.1
4000	65.7	77.2	141.0	1129.3	349.8
4200	69.0	81.0	148.1	1184.0	366.5
4250	69.8	82.0	149.9	1197.8	370.7
4400	72.2	84.8	155.2	1238.7	383.2
4500	73.9	86.8	158.8	1266.0	391.6
4600	75.5	88.7	162.3	1293.4	399.9
4750	77.9	91.5	167.6	1331.2	412.5